

**Canon**

imagePROGRAF

PRO Series

**THE PRINTERS THAT ARE EQUALLY OBSESSED.**



imagePROGRAF PRO-2600



imagePROGRAF PRO-4600



imagePROGRAF PRO-6600

# The Canon Story

Exceptional Quality, Precise Reproduction, and Extraordinary Colors



The imagePROGRAF PRO-4600 and PRO-2600 shown with optional multifunction roll unit.

## Printer

Professional photographers, graphic designers, and more desire a wide color gamut that accurately reproduces even the most difficult colors. From stunning black-and-white prints with deep blacks, detailed gradations to extraordinary color, the Canon imagePROGRAF PRO Series is designed to achieve it all.

The imagePROGRAF 60" PRO-6600, 44" PRO-4600, and 24" PRO-2600 professional large-format printers offer an 11-Color plus Chroma Optimizer ink system that can bring your prints and reproductions to life. With intelligent media handling and color calibration technologies, these are the most advanced large format printers Canon has engineered yet.



## Camera

Your photography deserves a printer worthy of your creative vision, with quality output to match. Just like many of our interchangeable L-Series lenses, the imagePROGRAF PRO Series printers are distinguished with a bold red line.

For professional photographers and graphic designers, exquisite prints with impeccable details are a must. With the latest imagePROGRAF PRO Series and the newly reformulated LUCIA PRO II ink, you can produce stunning results filled with vibrant colors or intricate black-and-white prints which make them timeless.



© Joel Grimes, Canon Explorer of Light

## Newly Formulated

The Matte Black ink is the same ink formulation as the imagePROGRAF GP-4000/2000

## Features

### New LUCIA PRO II Ink

Designed to produce vivid color prints with more accurate color reproduction and improved black density color output than predecessor models.

### Achievable Output

- Improved black density with a wide dark-color gamut range
- High scratch resistance
- Excellent light resistance for long-term preservation of prints

### Color Calibration

This helps ensure your output is color consistent over time and across multiple imagePROGRAF PRO Series devices.

### Media Handling

- Intelligent media handling helps reduce time and waste
  - Automatic media feeding
  - Automatic media type, width, and length detection
  - Reduced media feed processing time from previous imagePROGRAF PRO Series models
- Multifunction Roll Unit
  - Standard with the imagePROGRAF PRO-6600
  - Optional for the imagePROGRAF PRO-4600 and imagePROGRAF PRO-2600

### “Ease of Use” Body Design

- The user interface screen displays the ink levels, media indicator levels, and other setting prompts all on the home screen
- Easily see ink tanks and loaded media through translucent covers
- Interior LED light for reliable operation, such as previewing output while printing

### Environmentally Conscious

- EPEAT Gold®
- ENERGY STAR®




### Software

**Professional Print and Layout** enables easy professional photo printing with editing and layout tools, as well as color management capabilities.

**Free Layout Plus** is a print utility that lets you nest, tile, and create custom layouts before printing your files.

**Accounting Manager** helps track actual ink and media usage and costs.



© Darell Gullin, Canon Explorer of Light



© Larry Chen, Canon Explorer of Light

# Printer Specs: PRO-6600/4600/2600

## Print Head

PF-10

## Number of Nozzles

18,432 nozzles

## Droplet Size

4 pl per Color

## Ink Type

Pigment: BK, MBK, C, M, Y, PC, PM, GY, PGY, R, B, +CO

## Ink Tank

### Shipped with PRO-2600:

160 ml of each color MBK, BK, C, M, Y, GY, O, PC, PM, R, B, CO

### Shipped with PRO-4600:

330 ml of each color MBK, BK, C, M, Y, GY, O, PC, PM, R, B, CO

### Shipped with PRO-6600:

330 ml of each color MBK, BK, C, M, Y, GY, O, PC, PM, R, B, CO

### Replacement:

160 ml PFI-3100 (BK, C, M, Y, GY, PC, PM, R, B, CO), 160 ml PFI-2100 (MBK, O)

330 ml PFI-3300 (BK, C, M, Y, GY, PC, PM, R, B, CO), 330 ml PFI-2300 (MBK, O)

700 ml PFI-3700 (BK, C, M, Y, GY, PC, PM, R, B, CO), 700 ml PFI-2700 (MBK, O)

## Printer RAM

Standard Memory: 3 GB

Hard Disk: 500 GB

## Media Feed

**PRO-6600:** Front-Loading Roll Feed: Two\* Rolls, Front Output

**PRO-4600:** Front-Loading Roll Feed: One Roll, Front Output

**PRO-2600:** Front-Loading Roll Feed: One Roll, Front Output

**Cut Sheet:** Upper-loading, Front Output (Manual feed using media locking lever)

## Media Width

### PRO-2600:

Roll Feed: 6"-24" (152.4-610 mm)

Cut Sheet: 6"-24" (152.4-610 mm)

### PRO-4600:

Roll Feed: 6"-44" (152.4-1,118 mm)

Cut Sheet: 6"-44" (152.4-1,118 mm)

### PRO-6600:

Roll Feed: 6"-60" (152.4 mm - 1,524 mm)

Cut Sheet: 6"-60" (152.4 mm - 1,524 mm)

## Media Cutter

Automatic horizontal cutting (Rotary cutter): standard

## Media Thickness

0.002" - 0.03" (0.07 mm - 0.8 mm)

## Media Core Sizes

2" Core Standard. 2"/3" Core Roll Holder Set PRO-2600 (RH2-29), PRO-4600 (RH2-46), PRO-6600 (RH2-66)

## Maximum Roll Outer Diameter

6.7" or less (170 mm or less)

## Media Output

Catch Basket

## Printing Software Utilities

Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Canon Print Service, Professional Print & Layout

## Operating System

Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit),

Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit),

Macintosh OS v10.12.6 - v13x

## Print Language

Printer: SGRaster (Swift Graphic Raster), PDF, JPEG

## Interface

Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n) ■

## Power Supply

AC 100 - 240V (50 - 60 Hz)

## Power Consumption

Max: Approx 85W

Standby: Approx. 1.7W | Power Off: Approx 0.1W

## Certifications

ENERGY STAR® (Worldwide), EPEAT Gold

## Operational Environment

Temperature: 59 - 86 °F (15 - 30 °C)

Relative Humidity: 10 - 80% (Non Condensation)

## Printer Dimensions (W x D x H) and Weight

**PRO-2600:** (with stand and basket open) 43.7" x 38.7" x 46", 225 lbs

**PRO-4600:** (with stand and basket open) 62.7" x 38.7" x 46", 273.4 lbs

**PRO-6600:** (with stand and basket open) 78.7" x 38.7" x 46", 377 lbs

## Package Dimensions (W x D x H) and Weight

**PRO-2600:** (main unit with pallet) 52.1" X 35.9" X 44.8", 346.1lbs

**PRO-4600:** (main unit with pallet) 71.7" x 36" x 41", 407.9lbs

**PRO-6600:** (main unit with pallet) 87.7" x 36.0" x 40.4", 490 lbs

## Options

• Multifunction Roll Unit - PRO-2600 (RU-23) & PRO-4600 (RU-43)

• 2/3" Roll Holder Set PRO-2600

### User-Replaceable Items:

• Ink Tank: PFI-3100 (160 ml)/PFI-2100 MBK (160 ml), PFI-3300 (330 ml)/ PFI-2300 MBK (330 ml), PFI-3700 (700 ml)/PFI-2700 MBK (700 ml)

• Print Head (PF-10)

• Maintenance Cartridge (MC-30)

• Cutter Blade (CT-07)

## What's In The Box

### PRO-2600:

Printer, 160 ml Starter Ink Tanks, 1 Print Head, Maintenance Cartridge (Installed), 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, One Year Printer Warranty Statement, Print Head Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in)

### PRO-4600:

Printer, 330 ml Starter Ink Tanks, 1 Print Head, Maintenance Cartridge (Installed), 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, One Year Printer Warranty Statement, Print Head Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in)

### PRO-6600:

Printer, 330 ml Starter Ink Tanks, 1 Print Head, Maintenance Cartridge (Installed), Multifunction Roll Unit, 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, One Year Printer Warranty Statement, Print Head Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in)

- Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

\* If multifunction roll unit is used.

**WJS**  
759 Hill Street  
Jefferson, LA 70121  
(504) 837-5666  
www.wjsenterprises.com

**ENTERPRISES, INC.**

11725 Industriplex Blvd, #3  
Baton Rouge, LA 70809  
(225) 752-0957



Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues.

Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Some security features may impact functionality/performance; you may want to test these settings in your environment.

Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Wi-Fi is a registered trademark of the Wi-Fi alliance. All other referenced product names and marks are trademarks of their respective owners. All printer output and screen images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2024 Canon U.S.A., Inc. All rights reserved.

1/24/23-2562-9840