



Product guide

HP LaserJet Enterprise X600 Monochrome Managed Printers Series

The ultimate A4 enterprise printer for large teams

Built to simplify document workflows and handle high-volume printing with blazing-fast speeds and customizable features. It integrates effortlessly with your existing fleet, is future-ready with upgradable solutions, and is the world's most secure to protect your data.¹



Get the power to be more productive



Simplify work with automated workflows



The world's most secure printing technology¹



Save energy and help reduce waste

HP LaserJet Enterprise X600 Series comparison



Model	HP LaserJet Enterprise X60257dn ⁵	HP LaserJet Enterprise X60357dn ⁶
Product Number	A29ZDA	675T3A
Functions	Print	Print
Print speed (up to) ²	57/55 ppm (Letter/A4)	57/55 ppm (Letter/A4)
Auto 2-sided printing	Yes	Yes
Connectivity	USB, Ethernet	USB, Ethernet
Walk-up USB	No	Yes
Control panel	2.7" Non-touch	4.3" Color Touchscreen
Input capacity	650/2,850 (std/max)	650/2,850 (std/max)
Memory and Storage*	2GB RAM, 8GB eMMC	4GB RAM, 32GB eMMC
RMPV ⁴	10,000 to 25,000	15,000 to 37,500
Workpath enabled	No	Yes
Extensibility	HP FutureSmart ³ , OXPd	HP FutureSmart ³ , OXPd

Footnotes

1. Solutions deployed through the Hardware Integration Pocket (HIP) may require additional purchase.
2. Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
3. Some features enabled by future HP FutureSmart firmware upgrades may not be available on older devices, if for example, physical product characteristics limit the functionality of the new feature.
4. HP recommends that the number of pages per month of imaged output be within a stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period, the lowest monthly volume shown is based on 60-month usage and the highest 24-month usage.
5. Available in AMS and APJ only.
6. Not available in India

*Optional storage options are available depending on configuration. Please contact your HP representative for details.



HP LaserJet Enterprise X60257dn Printer

Processor speed	Dual Core (1.4 GHz)			
Orderable supplies	HP LaserJet Transfer Roller Kit C35T5A; HP LaserJet Tray Roller Kit C35T6A			
Printer Smart Software Features	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs			
Power Consumption Description	760 watts (Printing), 7.5 watts (Ready), 0.93 watts (Sleep), 0.05 watts (Auto-Off), 0.05 watts (Off)			
Power Supply	Type	Built-in 3-Pin 115V or 220V Internal Power Supply	Required	Input Voltage: 100V - 127V AC, 50 - 60Hz, 9.7A; or Input Voltage: 220V - 240V AC, 50 - 60Hz, 5.0A
What Is In The Box	HP LaserJet Enterprise X60257DN PRINTER; HP Original LaserJet Toner Cartridge (~10k page yield); Documentation (Hardware Install Guide, regulatory flyer); Power cord			
Replacement Cartridges	HP Black Managed LaserJet Toner (42,000 yield) W9088MC.			
Supplies Feature	HP TerraJet Cartridge			
Electromagnetic Emission Standard	CISPR 22:2008 (International) Class A, CISPR 32:2015 (International) Class A / EN 55032:2015 Class A + A11:2020; CISPR 35:2016 (International) / EN 55035:2017 + A11:2020, EN IEC 61000-3-2:2019 + A11:2020, EN IEC 61000-3-3:2013+A1:2019 + A2:2021, FCC 47 CFR Part 15 Class A, ICES-003, Issue 7 Class A. Other EMC approvals as required by individual countries.			
Safety Approvals and Requirements	IEC 62368-1:2014; EN 62368-1:2014 +A11:2017; IEC 62368-1:2018; EN 62368-1:2020 +A11:2020; EN 60825-1:2014 +A11:2021/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); UL62368-1 3rd Ed. 2021-10-22, CSA C22.2 No. 62368-1-19, 3rd Ed.; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 56, Dated May 8, 2019; Other safety approvals as required by individual countries.			
Energy Star Certified	Yes			
Ecolabels	CECP; IT ECO Declaration; Blue Angel; EPEAT® Gold India; EPEAT® Gold Australia; EPEAT® Gold Canada; EPEAT® Gold US; SEPA; KOECO; ENERGY STAR® certified; Korea MEPS; Vietnam MEPS			
Blue Angel Compliance	Blue Angel DE-UZ 219—only ensured when using Original HP supplies			
Sustainable Impact Specifications	Recyclable through HP Planet Partners; Contains at least 5% post-consumer recycled plastic			
Network Capabilities	Via HP Jetdirect Ethernet embedded print server (standard) which supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); WiFi 2.4/5 GHz wireless networking (optional); Second Ethernet port (optional); Microsoft Universal Print (MUP).			

HP LaserJet Enterprise X60257dn Printer

Supported Network Protocols	Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint, FTP Print, Google Cloud Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual, TFTP Config, ARP-Ping), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/v3, HTTP/HTTPS, Telnet, TFTP Config, FTP FW Download, Syslog; Security: SNMPv3, SSL Cert Management, Firewall, ACL, 802.1x	
Package dimensions Metric	Metric - 493 x 565 x 442 mm	Imperial - 19.41 x 22.24 x 17.4 in
Product dimensions Metric	Metric - 400 x 400 x 340 mm	Imperial - 15.7 x 15.7 x 13.4 in
Display description	400 x 400 x 340 mm	
Acoustic pressure emissions (active, printing)	6.8 B(A)	
Acoustic pressure emissions bystander	3.2 B(A)	
Operating humidity	10 to 80% RH	
Operating humidity (recommended)	30 to 70% RH	
Operating temperature range	Celsius: 15 to 30°C	Fahrenheit: 59 to 86°F
	Recommended Celsius: 17.5 to 25°C	Recommended Fahrenheit: 63.5 to 77°F
Storage Temperature Range	Celsius: -20 to 40°C	Fahrenheit: -4 to 104°F
Memory	2 GB	
Print Resolution Technologies	Normal (600x600 dpi with FastRes), Fine Lines (1200x1200 dpi), Quickview (300x300 dpi)	
Print speed	Up to 57 ppm	
First Page Out	Black (A4, ready) As fast as 3.9 seconds	Black (Letter, ready) As fast as 3.7 seconds
Monthly duty cycle	A4 - Up to 310,000 pages	Letter - Up to 310,000 pages
Recommended Monthly Page Volume*	10,000 to 25,000	
Fonts and Typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); Additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at http://www.hp.com/go/laserjetfonts	
Storage	Standard: 32 GB eMMC; Optional: 512 GB SSD	
Print Languages, Standard	HP PCL 6, HP PostScript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™	
Printer Management	HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP Security Manager; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)	
Top Key Features	Two-sided printing; TerraJet cartridge	
Target Number of Users and Print Volume	For teams over 25 users; Prints up to 25,000 pages/month	
AIO Functions	Print	
Duplex Print Options	Automatic (standard)	
Print Technology	Laser	

HP LaserJet Enterprise X60257dn Printer

Paper Handling Optional/input	Optional: 1 x 550-sheet paper feeder, 1 x 550-sheet feeder with cabinet, 3 x 550-sheet feeder, envelope feeder kit	
Paper Handling Standard/input	100-sheet multipurpose feeder, 550-sheet input feeder	
Paper Handling Standard/output	500-sheet output feeder	
Input Capacity, Max	Up to 2850 sheets	
Product Short Name	X60257dn	
Typical Electricity Consumption (TEC) number	0.528 kWh/Week (Blue Angel); 0.621 kWh/Week (ENERGY STAR 3.0)	
Number of Simultaneous Users (local + network)	10-30 Users	
Security Management	Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solutions (e.g.; badge readers); Network: IPsec/firewall with Certificate, Pre-Shared Key, and Kerberos authentication; Supports WJA-10 IPsec configuration Plug-in; 802.1X authentication (EAP-PEAP; EAP-TLS); SNMPv3; HTTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft); Secure Erase; SSL/TLS (HTTPS); Encrypted Credentials; Device: Security lock slot; USB port disablement; hardware integration pocket for security solutions; Hardware-based Memory Shield™ with Control Flow Integrity (CFI) in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing capability; Whitelisting - loads only known good code (DLLs, EXEs, ...); Security management: Compatible with Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs	
Mac Compatible	Yes	
Software Included	No software solutions are included in the Box, only on http://hp.com ;	
Media Types	Paper (plain, light, bond, recycled, heavy, extra heavy, cardstock, pre-printed, pre-punched, colored, rough, heavy rough), mono transparency, labels, letterhead, envelope, heavy envelope	
Standard Media Sizes	Metric - Tray 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340), 16K, postcards (JIS single and double), envelopes (B5, C5, C6, DL); Tray 2: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), Oficio (216 x 340), 16K, postcards (JIS double); Optional 550-sheet Tray: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), Oficio (216 x 340), 16K, postcards (JIS double); Optional Automatic Duplexer: A4, RA4, Oficio (216 x 340); Envelope Feeder Accessory: B5, C5, C6, DL	Imperial - Tray 1: Letter, Legal, Executive, Statement, 3 x 5 in, 4 x 6 in, 5 x 7 in, 5 x 8 in, 8.5 x 13 in, Envelopes (No. 9, No. 10, Monarch); Tray 2: Letter, Legal, Executive, Statement, 5 x 7 in, 5 x 8 in, 8.5 x 13 in; Optional 550-Sheet Tray: Letter, Legal, Executive, Statement, 5 x 7 in, 5 x 8 in, 8.5 x 13 in; Optional Automatic Duplexer: Letter, Legal, 8.5 x 13 in; Envelope Feeder Accessory: No. 9, No. 10, Monarch
Media sizes custom	Metric - Standard Optional Paper Feeder: A4; A5; A6; RA4; B5 (JIS); B6 (JIS); Oficio (216 x 340); 16K; postcards (JIS double); 105 x 148 to 216 x 356 mm; Envelope Feeder Accessory: Envelopes; 98 x 162 to 178 x 254 mm	Imperial - Tray 1: 3 x 5 to 8.5 x 14 in; Tray 2: 4.14 x 5.83 to 8.5 x 14 in; Optional 550-sheet Tray: 4.14 x 5.83 to 8.5 x 14 in; Envelope Feeder Accessory: 3.86 x 6.38 to 7 x 10 in
Media Size, Tray 1 (metric)	A4; A5; A6; RA4; B5 (JIS); B6 (JIS); 10 x 15 cm; Oficio (216 x 340); 16K; postcards (JIS single and double); envelopes (B5, C5, C6, DL); 76 x 127 to 216 x 356 mm	
Media weights supported, by paper path	Metric - Feeder 1: 60 to 200 g/m ² ; Feeder 2: 60 to 120 g/m ² ; Automatic Duplexer: 60 to 120 g/m ²	Imperial - Feeder 1: 16 to 53 lb bond (plain), 16 to 24 lb (envelopes); Feeder 2: 16 to 32 lb bond (plain); Automatic Duplexer: 16 to 32 lb



HP LaserJet Enterprise X60257dn Printer

Media Weights Supported, Tray 1 (metric)	60 to 200 g/m ²	
Key media sizes supported	Metric - A4; Envelopes; A5	Imperial - 4 x 6 in; Letter; Legal; Envelopes; 3 x 5 in
Control Panel	2.7-in (6.86 cm) Non-touch QVGA LCD (color graphics) display with 24-key pad	
System Requirements	Minimum - 2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com	Macintosh Minimum - 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com
Manufacturer Warranty	One-year, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (warranty code 4G; warranty ID A001)	
Package weight	Metric - 17.7 kg	Imperial - 39.02 lb
Weight	Metric - 12.8 kg	Imperial - 28.2 lb

HP LaserJet Enterprise X60357dn Printer

Processor Speed	Dual Core (1.4 GHz)			
Orderable Supplies	HP LaserJet Transfer Roller Kit C35T5A; HP LaserJet Tray Roller Kit C35T6A			
Printer Smart Software Features	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB			
Power Consumption Description	760 watts (Printing), 7.5 watts (Ready), 0.93 watts (Sleep), 0.05 watts (Auto-Off), 0.05 watts (Off)			
Power Supply	Type	Built-in 3-Pin 115V or 220V Internal Power Supply	Required	Input Voltage: 100V - 127V AC, 50 - 60Hz, 9.7A; or Input Voltage: 220V - 240V AC, 50 - 60Hz, 5.0A
What Is In The Box	HP LaserJet Enterprise X60357DN PRINTER; HP Original LaserJet Toner Cartridge (~10k page yield); Documentation (Hardware Install Guide, regulatory flyer); Power cord			
Replacement Cartridges	HP Black Managed LaserJet Toner (42,000 yield) W9088MC.			
Supplies Feature	HP TerraJet Cartridge			
Electromagnetic Emission Standard	CISPR 22:2008 (International) Class A, CISPR 32:2015 (International) Class A / EN 55032:2015 Class A + A11:2020; CISPR 35:2016 (International) / EN 55035:2017 + A11:2020, EN IEC 61000-3-2:2019 +A11:2020, EN IEC 61000-3-3:2013+A1:2019 + A2:2021, FCC 47 CFR Part 15 Class A, ICES-003, Issue 7 Class A. Other EMC approvals as required by individual countries.			
Safety Approvals and Requirements	IEC 62368-1:2014; EN 62368-1:2014 +A11:2017; IEC 62368-1:2018; EN 62368-1:2020 +A11:2020; EN 60825-1:2014 +A11:2021/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); UL62368-1 3rd Ed. 2021-10-22, CSA C22.2 No. 62368-1-19, 3rd Ed.; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 56, Dated May 8, 2019; Other safety approvals as required by individual countries.			
Energy Star Certified	Yes			
Ecolabels	CECP; IT ECO Declaration; Blue Angel; EPEAT® Gold India; EPEAT® Gold Australia; EPEAT® Gold Canada; EPEAT® Gold US; SEPA; KOECO; ENERGY STAR® certified; Korea MEPS; Vietnam MEPS			
Blue Angel Compliance	Blue Angel DE-UZ 219—only ensured when using Original HP supplies			
Sustainable Impact Specifications	Recyclable through HP Planet Partners; Contains at least 5% post-consumer recycled plastic			
Network Capabilities	Via HP Jetdirect Ethernet embedded print server (standard) which supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); WiFi 2.4/5 GHz wireless networking (optional); Second Ethernet port (optional); Microsoft Universal Print (MUP).			

HP LaserJet Enterprise X60357dn Printer

Supported Network Protocols	Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint, FTP Print, Google Cloud Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual, TFTP Config, ARP-Ping), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/v3, HTTP/HTTPS, Telnet, TFTP Config, FTP FW Download, Syslog; Security: SNMPv3, SSL Cert Management, Firewall, ACL, 802.1x	
Mobile Printing Capability	Apple AirPrint™; Mopria™ certified	
Digital sending standard features	NA	
Package dimensions Metric	Metric - 493 x 565 x 442 mm	Imperial - 19.41 x 22.24 x 17.4 in
Max. dimensions Metric	Metric - 400 x 725 x 340 mm (control panel fully upright, rear jam access door open, front cartridge door open, all feeders open and extended)	Imperial - 15.7 x 28.5 x 13.4 in (control panel fully upright, rear jam access door open, front cartridge door open, all feeders open and extended)
Product dimensions Metric	Metric - 400 x 400 x 340 mm	Imperial - 15.7 x 15.7 x 13.4 in
Display description	400 x 400 x 340 mm	
Acoustic pressure emissions (active, printing)	6.8 B(A)	
Acoustic pressure emissions bystander	3.2 B(A)	
Operating humidity	10 to 80% RH	
Operating humidity (recommended)	30 to 70% RH	
Operating temperature range	Celsius: 15 to 30°C	Fahrenheit: 59 to 86°F
	Recommended Celsius: 17.5 to 25°C	Recommended Fahrenheit: 63.5 to 77°F
Storage Temperature Range	Celsius: -20 to 40°C	Fahrenheit: -4 to 104°F
Memory	4 GB	
Print Resolution Technologies	Normal (600x600 dpi with FastRes), Fine Lines (1200x1200 dpi), Quickview (300x300 dpi)	
Print speed	Up to 57 ppm	
First Page Out	Black (A4, ready) As fast as 3.9 seconds	Black (Letter, ready) As fast as 3.7 seconds
Monthly duty cycle	A4 - Up to 310,000 pages	Letter - Up to 310,000 pages
Recommended Monthly Page Volume*	15,000 to 37,500	
Fonts and Typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); Additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at http://www.hp.com/go/laserjetfonts	
Storage	Standard: 32 GB eMMC; Optional: 512 GB SSD	
Print Languages, Standard	HP PCL 6, HP PostScript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™	
Printer Management	HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP Security Manager; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)	
Top Key Features	Two-sided printing; TerraJet cartridge; Front USB flash drive port	

HP LaserJet Enterprise X60357dn Printer

Target Number of Users and Print Volume	For teams over 25 users; Prints up to 37,500 pages/month
Fonts and Typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP postscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation information available in the user guide and documentation for this printer model at http://www.hp.com/support .
Hard Disk	Standard, 32GB eMMC; Optional, minimum 500 GB HDD; Optional, 512 GB SSD
Print Languages, Standard	HP PCL 6, HP PostScript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™
Printer Management	HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP Security Manager; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)
Top Key Features	Two-sided printing; TerraJet cartridge; Front USB flash drive port
Target Number of Users and Print Volume	For teams over 25 users; Prints up to 37,500 pages/month
AIO Functions	Print
Duplex Print Options	Automatic (standard)
Print Technology	Laser
Paper Handling Optional/input	Optional: 1 x 550-sheet paper feeder, 1 x 550-sheet feeder with cabinet, 3 x 550-sheet feeder, envelope feeder kit
Paper Handling Standard/input	100-sheet multipurpose feeder, 550-sheet input feeder
Paper Handling Standard/output	500-sheet output feeder
Input Capacity, Max	Up to 2850 sheets
Product Short Name	X60357dn
Typical Electricity Consumption (TEC) number	0.528 kWh/Week (Blue Angel); 0.621 kWh/Week (ENERGY STAR 3.0)
Number of Simultaneous Users (local + network)	10-30 Users
Security Management	Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solutions (e.g.; badge readers); Network: IPsec/firewall with Certificate; Pre-Shared Key; and Kerberos authentication; Supports WJA-10 IPsec configuration Plug-in; 802.1X authentication (EAP-PEAP; EAP-TLS); SNMPv3; HTTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft); Secure Erase; SSL/TLS (HTTPS); Encrypted Credentials; Device: Security lock slot; USB port disablement; hardware integration pocket for security solutions; Hardware-based Memory Shield™ with Control Flow Integrity (CFI) in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing capability; Whitelisting - loads only known good code (DLLs, EXEs, ...); Security management: Compatible with Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs
Mac Compatible	Yes
Software Included	No software solutions are included in the Box, only on http://hp.com ;

HP LaserJet Enterprise X60357dn Printer

Media Types	Paper (plain, light, bond, recycled, heavy, extra heavy, cardstock, pre-printed, pre-punched, colored, rough, heavy rough), mono transparency, labels, letterhead, envelope, heavy envelope	
Standard Media Sizes	Metric - Tray 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340), 16K, postcards (JIS single and double), envelopes (B5, C5, C6, DL); Tray 2: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), Oficio (216 x 340), 16K, postcards (JIS double); Optional 550-sheet Tray: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), Oficio (216 x 340), 16K, postcards (JIS double); Optional Automatic Duplexer: A4, RA4, Oficio (216 x 340); Envelope Feeder Accessory: B5, C5, C6, DL	Imperial - Tray 1: Letter, Legal, Executive, Statement, 3 x 5 in, 4 x 6 in, 5 x 7 in, 5 x 8 in, 8.5 x 13 in, Envelopes (No. 9, No. 10, Monarch); Tray 2: Letter, Legal, Executive, Statement, 5 x 7 in, 5 x 8 in, 8.5 x 13 in; Optional 550-Sheet Tray: Letter, Legal, Executive, Statement, 5 x 7 in, 5 x 8 in, 8.5 x 13 in; Optional Automatic Duplexer: Letter, Legal, 8.5 x 13 in; Envelope Feeder Accessory: No. 9, No. 10, Monarch
Media sizes custom	Metric - Standard Optional Paper Feeder: A4; A5; A6; RA4; B5 (JIS); B6 (JIS); Oficio (216 x 340); 16K; postcards (JIS double); 105 x 148 to 216 x 356 mm; Envelope Feeder Accessory: Envelopes; 98 x 162 to 178 x 254 mm	Imperial - Tray 1: 3 x 5 to 8.5 x 14 in; Tray 2: 4.14 x 5.83 to 8.5 x 14 in; Optional 550-sheet Tray: 4.14 x 5.83 to 8.5 x 14 in; Envelope Feeder Accessory: 3.86 x 6.38 to 7 x 10 in
Media Size, Tray 1 (metric)	A4; A5; A6; RA4; B5 (JIS); B6 (JIS); 10 x 15 cm; Oficio (216 x 340); 16K; postcards (JIS single and double); envelopes (B5, C5, C6, DL); 76 x 127 to 216 x 356 mm	
Media weights supported, by paper path	Metric - Feeder 1: 60 to 200 g/m ² ; Feeder 2: 60 to 120 g/m ² ; Automatic Duplexer: 60 to 120 g/m ²	Imperial - Feeder 1: 16 to 53 lb bond (plain), 16 to 24 lb (envelopes); Feeder 2: 16 to 32 lb bond (plain); Automatic Duplexer: 16 to 32 lb
Media Weights Supported, Tray 1 (metric)	60 to 200 g/m ²	
Key media sizes supported	Metric - A4; Envelopes; A5	Imperial - 4 x 6 in; Letter; Legal; Envelopes; 3 x 5 in
Control Panel	4.3-in (10.92 cm) Color Graphics Display (CGD) with touchscreen	
System Requirements	Minimum - 2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com	Macintosh Minimum - 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com
Manufacturer Warranty	One-year, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (warranty code 4G; warranty ID A001)	
Package weight	Metric - 17.7 kg	Imperial - 39.02 lb
Weight	Metric - 12.9 kg	Imperial - 28.2 lb

Paper handling accessories

Stand and input devices



Product number	6C7M6A	B01KLA	B01KTA	B01KSA
Product description	HP LaserJet 550 sheet paper tray	HP LaserJet 3x550 Sheet Paper Tray with Stand	HP LaserJet 550 Sheet Paper Tray with Storage Stand	HP LaserJet Envelope Feeder Kit
Configurations	Available as optional accessory			
Stacking Configurations	<ul style="list-style-type: none"> Desktop configuration - 2 trays max Floorstanding configuration- varies 	Floor standing unit plus max of 1 additional 1 x 550 tray allowed	Floor standing unit plus max of 2 additional 1 x 550 tray allowed	If tray 3 is available

Footnotes

1. HP's most advanced embedded security features are available on HP Managed and Enterprise devices with HP FutureSmart firmware 4.5 or above. Claim based on HP review of published features as of June 2025 of competitive in-class printers. Only HP offers a combination of security features to automatically detect, isolate, stop, and recover from attacks with a self-healing reboot, in alignment with NIST SP 800-193 guidelines for device cyber resiliency. Printers are most vulnerable to attack when they are booting up and during runtime (when the printer is in sleep mode and in use). Only HP Enterprise printers protect the device during 100% of the printer's life with Sure Start BIOS protection, Memory Shield with hardware-based Runtime Intrusion Detection and Control Flow Integrity to detect and recover from zero-day threats in addition to Connection Inspector network behavioral anomaly detection all with self-healing recovery. For a list of compatible products, visit hp.com/go/PrintersThatProtect For more information, visit hp.com/go/PrinterSecurityClaims.

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

c09247849

